

luminous flux:	2000 lm	1500 lm
maximum power:	22W	18W
rated voltage:	12÷24V DC	
permissible voltage:	10,5÷30V DC	
current at 13,2V:	1,6A	1,1A
current at 28V:	0,9A	0,6A
maximum current:	1,6A	1,1A
colour temperature:	6000÷6500K	5000÷5500K
beam:	spot	
beam angle:	4°	
IP rating:	IP67, IP69K, IP66	
work temperature:	-40°C ÷ 80°C	
housing's material:	aluminium	
lens' material:	plastic	
corrosion resistance:	ISO 9227, 500h	
vibration resistance:	15,3G 24÷2000Hz	
EMC Class CISPR 25:	V	
built-in connectors:	AMP Faston 250, Deutsch DT, AMP SuperSeal 1,5	
other:	protection: - against overheating - against reverse polarisation	

The lamps comply with EMC Directive 2004/108/EC.
They do not emit electromagnetic interference as well as they are resistant to it's influence.
Correct polarity required.
Mounting: as a freestanding on body panels.
The bracket parts are made of Inox steel.
Different colours of the frame are available: i.e. red, yellow (option).
It is possible to install needed connectors for a version with cable (on request).
Useful parts while installing:
Deutsch plug DT06-2S 2-pin - cat. No. A.07135
AMP SuperSeal 1,5 plug 2-pin - cat. No. A.07137
AMP Faston 250 plug 2-pin - cat. No. A.07138



Cat. number	Luminous flux		Colour temperature	6000÷6500K	5000÷5500K	IP rating	IP66	IP67	IP69K	Accessories	LED module 12V-24V	cable 0,5 m	Mounting method	installed vertically up	suspended	side	Bracket	M8	omega	Connectors	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	H9-H11	Cap / Pin	Packaging / pc	carton box
	2000 lm	1500 lm																									
CRV2D.56200	✓			✓				✓	✓		✓	✓		✓	✓		✓				✓					1	
CRV2D.56206	✓			✓			✓		✓		✓		✓	✓	✓		✓				✓				2	1	
CRV2D.56207	✓			✓				✓	✓		✓		✓	✓	✓		✓					✓			2	1	
CRV2D.56208	✓			✓				✓	✓		✓		✓	✓	✓		✓					✓			2	1	
CRV2D.56203	✓			✓				✓	✓		✓	✓	✓	✓	✓		✓						✓		2	1	
CRV2B.58700		✓			✓			✓	✓		✓	✓	✓	✓	✓		✓				✓					1	
CRV2B.58706		✓			✓		✓		✓		✓		✓	✓	✓		✓				✓				2	1	
CRV2B.58707		✓			✓			✓	✓		✓		✓	✓	✓		✓					✓			2	1	
CRV2B.58708		✓			✓			✓	✓		✓		✓	✓	✓		✓					✓			2	1	
CRV2D.56240	✓			✓				✓	✓		✓	✓				✓	✓									1	
CRV2D.56247	✓			✓				✓	✓		✓					✓	✓				✓				2	1	
CRV2B.58740		✓			✓			✓	✓		✓	✓				✓	✓									1	
CRV2B.58747		✓			✓			✓	✓		✓					✓	✓				✓				2	1	

